

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 03/25/2014 Date of issue: 03/25/2014 Version: 1.0

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

### 1.1. Product Identifier

**Product Name:** Enviro-Safe<sup>™</sup> Refrigerant with Dye 6 oz

### 1.2. Intended Use of the Product

Use of the Substance/Mixture: Refrigerant

### 1.3. Name, Address, and Telephone of the Responsible Party

### Company

DiY Parts, Inc. 3503 Holts Chapel Road Greensboro, NC 27401 336-560-7916 **1.4. Emergency Telephone Number** Emergency Number

: 1-800-424-9300

CHEMTREC - TOLL FREE 24 HOUR EMERGENCY TELEPHONE NUMBER

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P501 - Dispose of contents/container according to local, regional, national, and

### SECTION 2: HAZARDS IDENTIFICATION

2.1.	<b>Classification of the Substance or Mixture</b>
ol	

Classification (GHS-US) Simple Asphy Flam. Gas 1 H220 Liquefied gas H280 Skin Sens. 1 H317 2.2. Label Elements GHS-US Labeling Hazard pictograms (GHS-US)



Signal word (GHS-US) : Danger : H220 - Extremely flammable gas Hazard statements (GHS-US) H280 - Contains gas under pressure; may explode if heated H317 - May cause an allergic skin reaction May displace oxygen and cause rapid suffocation Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surfaces, open flames, sparks - Nosmoking. P261 - Avoid breathing gas. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear respiratory protection, cold insulating gloves, eye protection, protective clothing. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P321 - Specific treatment (see Section 4). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381 - Eliminate all ignition sources if safe to do so. P403 - Store in a well-ventilated place.

international regulations.

### 2.3. Other Hazards

Aquatic Chronic 3

H412 - Harmful to aquatic life with long lasting effects

P273 - Avoid release to the environment

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product Identifier	%	Classification (GHS-US)
Petroleum gases, liquefied	(CAS No) 68476-85-7	99	Simple Asphy
			Flam. Gas 1, H220
			Liquefied gas, H280
Odorant	Proprietary	.75	Flam. Liq. 3, H226
			Skin Irrit. 2, H315
			Skin Sens. 1, H317
			Aquatic Chronic 1, H410
Dye	Proprietary	.25	No Hazardous ingredients in accordance to
			EC regulations

Full text of H-phrases: see section 16

### SECTION 4: FIRST AID MEASURES

#### 4.1. **Description of First Aid Measures**

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Immediately call a POISON CENTER or doctor/physician.

First-aid Measures After Skin Contact: If frostbite or freezing occurs, immediately flush with plenty of lukewarm water to GENTLY warm the affected area. Do not use hot water. Do not rub affected area. Get immediate medical attention.

First-aid Measures After Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

First-aid Measures After Ingestion: Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: Gas can be toxic as a simple asphyxiant by displacing oxygen from the air.

Symptoms/Injuries After Inhalation: Asphyxiant gas.

Symptoms/Injuries After Skin Contact: May cause frostbite. Exposure may produce an allergic reaction.

Symptoms/Injuries After Eye Contact: Contact with the liquefied gas causes frostbite.

Symptoms/Injuries After Ingestion: Ingestion is an unlikely route of exposure for a gas.

### Indication of Any Immediate Medical Attention and Special Treatment Needed 4.3.

If exposed or concerned, get medical advice and attention.

## SECTION 5: FIREFIGHTING MEASURES

#### 5.1. **Extinguishing media**

Suitable extinguishing media	: Water spray, dry powder, or carbon dioxide can be directed at flame area to reduce fire intensity.
Unsuitable extinguishing media	: Do not extinguish flames unless leak can be stopped.
5.2. Special hazards arising fro	om the substance or mixture
Fire hazard	: Extremely flammable gas.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Reactivity	: Contains gas under pressure; may explode if heated.
5.3. Advice for firefighters	
Precautionary measures fire	: Exercise caution when fighting any chemical fire.
Firefighting instructions	: If possible, stop flow of gas. Use water to cool fire-exposed tanks, surroundings and to protect personnel working on shut off. If leak cannot be stopped, evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
07/25/2018	EN (English US) 2/7

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 6: ACCIDENTAL RELEASE MEASURES

SECTION 6: ACCIDENTAL	
• •	protective equipment and emergency procedures
General measures	: Use special care to avoid static electric charges. Keep away from open flames, hot surfaces and sources of ignition. No smoking. Do not get in eyes, on skin, or on clothing. Do not breathe gas.
6.1.1. For non-emergency perso	nnel
Protective equipment	: Use appropriate personal protection equipment (PPE).
Emergency procedures	: Evacuate unnecessary personnel. Eliminate ignition sources.
6.1.2. For emergency responder	'S
Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Stop leak if safe to do so. Ventilate area.
6.2. Environmental precaut	ions
Avoid release to the environment.	
6.3. Methods and material	for containment and cleaning up
For containment	: Stop leak without risks if possible.
Methods for cleaning up	: Contact competent authorities after a spill.
6.4. Reference to other sect	ions
See Section 8, Exposure Controls a	nd Personal Protection.
<b>SECTION 7: HANDLING A</b>	ND STORAGE
7.1. Precautions for safe ha	ndling
Precautions for safe handling	: Personnel should be trained to regularly inspect equipment such as pumps, hoses, and valves. Do not breathe gas. Ensure there is adequate ventilation. Close valve after each use and when empty. Open valve slowly to avoid pressure shock.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, o smoking and again when leaving work.
7.2. Conditions for safe stor	rage, including any incompatibilities
Technical measures	: Comply with applicable regulations. Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling. Keep at temperatures below 52°C / 125°F.
Storage conditions	<ul> <li>Store in a dry, cool and well-ventilated place. Keep in fireproof place. Store locked up. Store away from strong oxidizing agents, chlorine dioxide, excessive heat and/o static discharge.</li> </ul>
Incompatible products	: Heat sources. Oxidizing agents.
Special rules on packaging	: Store in containers fitted with suitable release valve.
7.3. Specific end use(s)	
Refrigerant.	
	ONTROLS/PERSONAL PROTECTION

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. **Control Parameters**

Petroleum gases, liquefied (68476-85-7)		
USA ACGIH	ACGIH TWA (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1800 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA IDLH	US IDLH (ppm)	2100 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) (mg/m³)	1800 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure Controls	
Appropriate engineering controls	: Alarm detectors should be used when toxic and/or flammable gases may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.
Personal protective equipment	: Gas mask. Protective goggles. Gloves. Protective clothing.
Materials for protective clothing	: Chemically resistant materials and fabrics.
Hand protection	: Wear working gloves when handling gas containers.
Eye protection	: Safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.
Thermal hazard protection	: Wear cold insulating gloves.
SECTION 9: PHYSICAL AND CHI	
9.1. Information on Basic Physical a	
Physical State	: Gas
Appearance	: Clear, colorless gas.
Odor	: Odoradded.
Odor Threshold	: No data available
рН	: No data available
Relative Evaporation Rate (butylacetate=1)	: No data available
Melting Point	: No data available
Freezing Point	: - 176.67 °C (- 286°F)
Boiling Point	: - 37.8 °C (- 36.1 °F)
Flash Point	: No data available
Auto-ignition Temperature	: 674.44 °C (1246 °F)
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: 482.6 kPa (70 psi) at 21.1 °C (70 °F)
Relative Vanor Density at 20 °C	· 164

Flammability (solid, gas)	: No data available
Vapor Pressure	: 482.6 kPa (70 psi) at 21.1 °C
Relative Vapor Density at 20 °C	: 1.64
Relative Density	: 0.53 (water = 1)
Specific Gravity	: 0.53
Solubility	: No data available
Log Pow	: <1
Log Kow	: No data available
Viscosity, Kinematic	: No data available
Viscosity, Dynamic	: No data available
Explosive Properties	: No data available
Oxidizing Properties	: No data available
Explosive Limits	: No data available
Lower Flammable Limit	: 2.6 %
Upper Flammable Limit	: 9%
9.2. Other Information	
Gas group	: Liquefied gas

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity: Contains gas under pressure; may explode if heated. Vapor may ignite if exposed to static discharge.

10.2 Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

10.3 Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

- 10.4 Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Open flame. Heat. Sparks. Static Discharge.
- **10.5** Incompatible Materials: Oxidizing agents such as chlorine, permanganates and dichromates.

**10.6** Hazardous Decomposition Products: Carbon oxides (CO, CO<sub>2</sub>).

### SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information On Toxicological Effects

Acute Toxicity : Not classified

Petroleum gases, liquefied (68476-85-7)

LC50 Inhalation Rat (mg/l)

658 mg/l/4h

### Skin Corrosion/Irritation: Not classified Serious Eye Damage/Irritation: Not classified

**Respiratory or Skin Sensitization**: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Asphyxiant gas.

Symptoms/Injuries After Skin Contact: May cause frostbite. Exposure may produce an allergic reaction.

Symptoms/Injuries After Eye Contact: Contact with the liquefied gas causes frostbite.

Symptoms/Injuries After Ingestion: Ingestion is an unlikely route of exposure for a gas.

### SECTION 12: ECOLOGICAL INFORMATION

- **12.1. Toxicity** Harmful to aquatic life with long lasting effects.
- 12.2. Persistence and Degradability No additional information available

### **12.3.** Bioaccumulative Potential

ZeroR <sup>™</sup> RZ134 a R134a Refrigerant Replacement 6 oz		
Log Pow	<1	
Petroleum gases, liquefied (68476-85-7)		
Log Pow	2.3	

**12.4.** Mobility in Soil No additional information available

### **12.5.** Other Adverse Effects

No additional information available

### SECTION 13: DISPOSAL CONSIDERATIONS

### **13.1.** Waste treatment methods

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Empty containers may contain flammable or combustible vapors. Do not reuse without adequate precautions.

### SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/IMDG/DOT

- 14.1. UN number None
- 14.2. UN proper shipping name Consumer Commodity, ORM-D
- 14.3. Additional information No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 15: REGULATORY INFORMATION**

### 15.1 US Federal Regulations

ZeroR A/C Chill a R134a Refrigerant Replacement 6 oz

SARA Section 311/312 Hazard Classes

Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard Sudden release of pressure hazard

Odorant (Proprietary)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Petroleum gases, liquefied (68476-85-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2 US State Regulations

### Odorant (Proprietary)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

### Petroleum gases, liquefied (68476-85-7)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)

U.S. - Delaware - Accidental Release Prevention Regulations - Sufficient Quantities

U.S. - Delaware - Accidental Release Prevention Regulations - Threshold Quantities

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities

U.S. - Idaho - Occupational Exposure Limits - TWAs

U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1

U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2

U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity

U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1

U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2

U.S. - Massachusetts - Right To Know List

U.S. - Michigan - Occupational Exposure Limits - TWAs

U.S. - Minnesota - Hazardous Substance List

U.S. - Minnesota - Permissible Exposure Limits - TWAs

U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances

U.S. - New Jersey - Environmental Hazardous Substances List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - New Jersey - Special Health Hazards Substances List

U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)

U.S. - New York - Occupational Exposure Limits - TWAs

U.S. - Ohio - Accidental Release Prevention - Threshold Quantities

U.S. - Oregon - Permissible Exposure Limits - TWAs

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Tennessee - Occupational Exposure Limits - TWAs

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

U.S. - Vermont - Permissible Exposure Limits - TWAs

U.S. - Washington - Permissible Exposure Limits - STELs

U.S. - Washington - Permissible Exposure Limits - TWAs

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 16: OTHER INFORMATION

- Revision date
- : 07/25/2018
- Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard
  - Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 3	Flammable liquids Category 3
Liquefied gas	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
H220	Extremely flammable gas
H226	Flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)